










## WAUSAU PRODUCT SELECTION TABLE

Product Series	Description	Frame Depth	Integral Blind Option	Thermal Barrier	Protective Glazing Certified	AAMA AW Class	 <b>WAUSAU</b> <small>WINDOW AND WALL SYSTEMS</small>		
<b>HUNG WINDOWS</b> (Recycled aluminum available upon request)									
310i-SH	Single Hung Side Load		Hung window for <b>high-performance</b> applications, with side load sash removable for cleaning.	3 ½"	No	15mm polyamide	-	AW 100	<b>Rigid five-member frame construction</b> facilitates installation, and reduces air infiltration. Durable Caldwell Ultralift® balances are standard.
3100-DH	Double Hung Side Load		<b>Standard double hung</b> window, with side load sash removable for cleaning.	4 ½"	Yes	Poured	-	AW 70	Direct and indirect double hung ventilation. Durable Caldwell Ultralift® balances are standard.
3150-DHT	Double Hung Tilt Sash		Double hung window, with <b>tilt-in sash</b> for cleaning.	4 ½"	Yes	Poured	-	AW 70	Direct and indirect double hung ventilation. Durable Caldwell Ultralift® balances are standard.
3151-ST	Single Hung Tilt Sash		Single hung window, with <b>tilt-in sash</b> for cleaning.	4 ½"	Yes	Poured	-	AW 75	Rigid five-member frame construction facilitates installation, and reduces air infiltration. Durable Caldwell Ultralift® balances are standard.
<b>HORIZONTAL ROLLING (Sliding) WINDOWS</b> (Recycled aluminum available upon request)									
2700/2760	Four-Track		<b>Dual</b> horizontal rolling window for <b>acoustical</b> applications, or for exterior polycarbonate vandalism glazing.	4 ½" or 6 ¼"	Yes	PVC	-	HC 40	Wide air spaces on 2760 option yield higher STC/OITC acoustical performance.
410i-HS	Single Slide		<b>True single slide</b> window for <b>high-performance</b> applications. Removable sash.	3 ½"	No	15mm polyamide	-	AW 70	<b>Rigid five-member frame construction</b> facilitates installation, and reduces air infiltration. Nylon rollers for smooth, quiet operation.
4100-HS	Double Slide		<b>Double "slide-by"</b> window for cleaning and operation in the plane of the wall.	4 ½"	Yes	Poured	-	AW 60	Nylon rollers for smooth, quiet operation.
4100i-HS	Double Slide		<b>Double "slide-by"</b> window for cleaning and operation in the plane of the wall. Two-color option.	4 ½"	Yes	15mm polyamide	-	AW 70	Nylon rollers for smooth, quiet operation.
General Notes (Hung and Rolling Windows): Check operating forces specific to window size and glass thickness.								©2009 Apogee Wausau Group	